
Oil press SPU 40 Specification

- Voltage: Single phase 1x230VAC or three phase 3x400VAC
- El.motor power: 2,2 kW
- Heater power: 800W
- Capacity : 8-40 kg/h of raw material
- Variable screw speed: 5 – 50 rpm
- Stand: Powder coated or stanless steel
- Weight: 103 kg
- Dimensions: 824 x 559 x 1012 mm
- All elements made of heat treated stainless steel
- Accessories: Adjustment tools 2 pcs, set of nozzles dia 4-15mm
- Three types of screw (Delivery with one screw - at the customer's choice)
- Application: on page 2



Application:

Shallow channel screw can be used for squeezing oil from the next raw materials

Hemp seeds

Flax seeds

Poppy seeds

Thistle seeds

Mustard seeds

Sesame seeds

Chia seeds

Sunflower seeds (peeled and unpeeled)

Rape seeds

Standard channel screw can be used for squeezing oil from the next raw materials

Poppy seeds

Chia seeds

Sunflower seeds (peeled and unpeeled)

Rape seeds

Apricot kernel

Plum kernel

Peanuts

Deep channel screw can be used for squeezing oil from the next raw materials

Rape seeds

Sunflower seeds (peeled and unpeeled)

Poppy seeds

Walnuts

Hazelnutts

Almonds

Apricot kernel

Plum kernel

Peanuts