
Oil press SPU 20 S

Specification

- Voltage: Single phase 1x230VAC or Three phase 3x400VAC
- El.motor power: 2,2kW
- Heater power: 600W
- Capacity : 5-20 kg/h of raw material
- Variable screw speed: 5 – 50 rpm
- Stand: Powder coated or stanless steel
- Weight: 86 kg
- Dimensions: 920 x 599 x 806 mm
- All elements made of heat treated stainless steel
- Accessories: Adjustment tools 2 pcs, set of nozzles dia 4-15mm
- Three types of screw (Delivery with one screw - at the customer's choice)
- Application: on page 2



Application:

Shallow channel screw can be used for squeezing oil from the next raw materials

Black grape seeds

White grape seeds

Pomegranate seeds

Hemp seeds

Flax seeds

Raspberry seeds

Blackberry seeds

Rose hip seeds

Strawberry seeds

Mulberry seeds

Poppy seeds

Thistle seeds

Black cumin seeds

Mustard seeds

Pumpkin seeds without shell

Sesame seeds

Chia seeds

Coconut flour (dried rendered coconut)

Sunflower seeds (peeled and unpeeled)

Rape seeds

Standard channel screw can be used for squeezing oil from the next raw materials

White grape seeds

Flax seeds

Poppy seeds

Thistle seeds

Mustard seeds

Pumpkin seeds without shell

Sesame seeds

Chia seeds

Sunflower seeds (peeled and unpeeled)

Coconut flour (dried rendered coconut)

Rape seeds

Walnuts

Hazelnutts

Almonds

Apricot kernel

Plum kernel

Peanuts

Deep channel screw can be used for squeezing oil from the next raw materials

Rape seeds

Sunflower seeds (peeled and unpeeled)

Poppy seeds

Walnuts

Hazelnutts

Almonds

Apricot kernel

Plum kernel

Peanuts