

EMS-PELLET D.O.O.

SENĆANSKA 80 23320 ČOKA, SERBIA Tel: 00381 230 315 960 office@ems-pellet.rs

Oil press SPU 20 Specification

- Voltage: Single phase 1x230VAC
- El.motor power: 1,5kW
- Heater power: 600W
- Capacity : 5-20 kg/h of raw material
- Variable screw speed: 5 50 rpm
- Stand: Powder caoted or stanless steel
- Weight: 66 kg
- Dimensions: 920 x 599 x 806 mm
- All elements made of heat treated stainless steel
- Accessories: Adjustment tools 2 pcs, set of nozzles dia 4-15mm
- Three types of screw (Delivery with one screw at the customer's choice)
- Application: on page 2



Application:

Shallow channel screw can be used for squeezing oil from the next raw materials Hemp seeds Flax seeds Poppy seeds Thistle seeds Black cumin seeds Mustard seeds Pumpkin seeds without shell Sesame seeds Chia seeds Coconut flour (dried rendered coconut) Sunflower seeds (peeled and unpeeled) Rape seeds

Standard channel screw can be used for squeezing oil from the next raw materials

Poppy seeds Thistle seeds Mustard seeds Sesame seeds Chia seeds Sunflower seeds (peeled and unpeeled) Rape seeds Almonds Apricot kernel Plum kernel Peanuts

Deep channel screw can be used for squeezing oil from the next raw materials

Rape seeds Sunflower seeds (peeled and unpeeled) Poppy seeds Walnuts Hazelnutts Almonds Apricot kernel Plum kernel Peanuts

Page 2